



FOLIANTEU, s.r.o.  
Stefanikova 1347/III  
293 01 Mlada Boleslav  
Czech Republic  
tel +420 326 370 711  
[foliant@foliant.eu](mailto:foliant@foliant.eu) | [www.foliant.eu](http://www.foliant.eu)

# FOLIANT VEGA 530S

The FOLIANT Vega 530S is a new generation of easy available very compact industrial laminating machines, designed for a heavy duty “In-House” lamination of digital and offset outputs (max. format 53 x 75 cm), in a semiautomatic configuration – manual feeding, automatic separation with a bump separator and adjustable twin decurl bar. Due to its pneumatic high pressure system (with integrated compressor inside machine frame), format and performance the machine is suitable for all jobs – all kinds of digital printed sheets lamination and high volumes of offset printed sheets size B2+ lamination too. **The machine maximum speed is up to 18 m/min.**, while performance is limited by the manual feeding only.



## FEEDING SECTION

The FOLIANT Vega 530S is equipped with an infeed table with synchronized belts and adjustable side guider for manual feeding. Due to upper overlapping, feeding belts and side guide, the manual feeding is easy.

## LAMINATOR

The FOLIANT Vega 530S laminator maximum sheet size is 53 x 75 cm. The minimum sheet size is 20 x 30 cm (A4). The FOLIANT Vega 530S machine is a single sided thermal industrial laminator, laminating the 115 – 500 gsm paper.

The machine does not need any external source of pressured air for the pneumatic pressure system, because the compressor is integrated inside the machine frame as a standard delivery.

The laminating unit is equipped with an adjustable twin decurl unit that can change angle during the operation:

- With a decurl blade for offset printed sheets decurling
- With a decurl roller for digital printed sheets decurling (to prevent the scratches on sheets printed on both sides by digital print with sensitive inks).

The roll of a film is mounted on a quick-changed shaft with a film tension control breaker. The shaft capacity is up to 3000 m of the 24 - 42 microns film. The film holder unit is equipped with an in-line trim slit and a perforating wheel.

The laminating process is made between two laminating rollers - a highly polished chrome roller, and a lower hard rubber pressure roller. The pressure is pneumatically adjustable. The laminating roller is heated with a dry electric system inside the roller, with a sensitive temperature sensor. The warming up time is shorter than 10 minutes.

The whole machine is controlled with an interactive, easy understandable icon based touch screen and its used control system includes many automation items for an easy control of the machine and a reliable lamination.

## SEPARATOR

The integrated bump separator (sheeter) is equipped with a pair of fast cycling rollers. The process is controlled from the machine control unit. The separated sheets are delivered into a vibrating jogger (optional) or adjustable reception unit (optional).

## LAMINATING FILMS

The machine laminates the BOPP films (24 – 42 µm). Nylon films (24 – 35 µm) can be processed with optional Pneumatic separation modification.

## OPTIONS

### JOGGER 530\*

It is an adjustable vibrating reception unit for the laminated sheets stocking. Its capacity is limited up to a 10 cm pile of sheets.

### RECEPTION UNIT 530\*

It is an adjustable desk for laminated sheets stocking. Its capacity is 10 cm pile of sheets.

### FOLIANT FOILER

Winding device that allows use of metalized film (gold, silver, red, etc.) and spot varnish film.

### NON-STICKY PRESSURE ROLLER

Standard rubber pressure roller is replaced by roller with non-sticky surface. Melted glue from film cannot stick to it even under heavy pressure. Cleaning of this roller is not necessary at all. Allows lamination of sheets with windows.

### EXTRA FILM SUPPLY ROLL SHAFT

Additional Film Supply Roll Shaft for quicker film replacement.

### PNEUMATIC SEPARATION

Standard mechanical separation system is replaced with pneumatically powered system. Advantage is in better control of the whole separation process. It is supplied with control valves for delay of separation and separation timing. This helps to separate thin sheets, thicker film, nylon film or helps with some other difficult jobs where fine tuning is necessary. Machine with this modification have to be connected to external pressurized air supply (6-8 bars, 50 l/min), it is supplied without compressor.

### AIR SHAFT

Standard film holder is replaced with air shaft for quick, tool-less film installation. Only available together with pneumatic separation option.

### ANTI-STATIC BAR

Pair of ionization bars that remove static charge from laminated paper.



Optional Jogger 530



Optional Foliant Foiler

\* Important - the machine must be operated either with Jogger or Reception unit

Foliant Vega 530S			
Max Speed	18 m / min	Warming up Time	8 min
Max Performance	1550 B2 / hour	Temperature Control	80 - 140°C
Feeding	Manual	Floor space with Jogger (w x l)	96 x 240 cm
Separation	Automatic, Bump Rollers	Weight	320 kg
Paper Weight	115 - 500 gsm	Twin Decurl Bar, In-Run Adjustable	Standard
Main Rollers Pressure	Pneumatic	Jogger 530	Optional
Integrated Compressor	Standard	Reception Unit RU530	Optional
Min. Sheets Size (w x l)	20 x 30 cm	Non-sticky pressure roller	Optional
Max. Sheets (w x l)	53 x 75 cm	Pneumatic separation	Optional
Power	2750 W	Air shaft	Optional
Power Supply	1 ph., 230-240 V AC, 50-60 Hz	Foliant Foiler	Optional