



FOLIANTEU, s.r.o.
Stefanikova 1347/III
293 01 Mlada Boleslav
Czech Republic
tel +420 326 370 711
foliant@foliant.eu | www.foliant.eu

FOLIANT VEGA 530 SF

The FOLIANT Vega 530 SF is a new generation of very compact industrial laminating machine, designed for a heavy duty "In-House" lamination of digital and offset outputs (max. format 53 x 75 cm). It is equipped with integrated deep pile suction feeder (original from offset printing machines), pneumatic high speed bump separator, adjustable dual decurl bar and overlap system. Due to its high pneumatic pressure system, format and performance the machine is suitable for all jobs – all kinds of digital printed sheets lamination and high volumes of offset printed sheets size B2+ lamination too. **The machine maximum speed is up to 20 m/min.**, while performance is almost 1720 sheets per hour of B2 portrait or 3000 sheets B3 landscape (blank paper 200 gsm).



FEEDER

The FOLIANT Vega 530 SF is equipped with a rising pile suction feeder. Its feeding head origin is in offset printing machines. The Becker vacuum pump integrated in the machine frame is used for sheets front airing. The overlaps are controlled, in an „in-run“ mode. The accuracy is +/- 2 mm under-lap (in a constant speed). The feeder is fitted with a lifting plate and its capacity is a 28 cm pile of paper.

LAMINATOR

The FOLIANT Vega 530A laminator maximum sheet size is 53 x 75 cm. The minimum sheet size is 20 x 30 cm (A4). The FOLIANT Vega 530A machine is a single sided thermal industrial laminator, laminating the 115 – 500 gsm paper.

The machine needs an external source of pressured air for the pneumatic pressure system 6 – 8 bar, 150 l/min.

The laminating unit is equipped with an adjustable dual decurl bar, in-run adjustable:

- With a decurl blade for offset printed sheets decurling
- With a decurl roller for digital printed sheets decurling (to prevent the scratches on sheets printed on both sides by digital print with a higher level of sensitive toners).

The whole machine is controlled with an interactive, easy understandable icon based touch screen and its used control system includes many automation items for an easy control of the machine and a reliable lamination.

More automation: Comparing competitive products Vega 530 SF machine's control system allows more automation like:

- Intelligent interruption of jobs, without any machine's re-installation or re-adjustment, it saves plenty of time
- First sheets of a new job automatic passing through the gap between master rollers, to the best position. It makes it safety and easy.
- Automatic regeneration of master pressure.

The roll of a film is mounted on a quick-changed shaft with a film tension control breaker. The shaft capacity is up to 3000 m of the 24 - 42 microns film. Standard core diameter: 76 mm. The film holder unit is equipped with an in-line trim splitter and a perforating wheel. The laminating process is made between two laminating rollers - a highly polished chrome roller, and a lower hard rubber pressure roller. The pressure is pneumatically adjustable. The laminating roller is heated with a dry electric system inside the roller, with a sensitive temperature sensor. The warming up time is shorter than 8 minutes.

SEPARATOR

The integrated pneumatic bump separator (sheeter) is equipped with a pair of fast cycling rollers. The process is controlled from the machine control unit. The separated sheets are delivered into a vibrating jogger (optional) or adjustable reception unit (optional).

LAMINATING FILMS

The machine laminates the BOPP films (24 – 42 µm) and Nylon films (24 – 35 µm).

OPTIONS

JOGGER 530*

It is an adjustable vibrating reception unit for the laminated sheets stocking. Its capacity is limited up to a 10 cm pile of sheets.

RECEPTION UNIT 530*

It is an adjustable desk for laminated sheets stocking. Its capacity is 10 cm pile of sheets.

FOLIANT FOILER

That system allows to stick (over digital printed toners) following foils:

- metalized foils (available in many designs like gold, silver, red etc.) and holographic foils
- transparent glossy foil for spot varnishing effect.

NON-STICKY PRESSURE ROLLER

It is a revolution in laminating technology – the standard rubber pressure roller is replaced by roller with non-sticky surface. It absolutely does not stick the glue. Film, inks and paper. Cleaning of this roller is not necessary at all. Allows lamination of sheets with windows.

EXTRA FILM SUPPLY ROLL SHAFT

Additional Film Supply Roll Shaft for quicker film replacement, film core 76 mm and 25 mm.

AIR SHAFT

Standard film holder is replaced with air shaft for quick, tool-less film installation, film core 76 mm only.

XXL FEEDING TABLE EXTENSION

Removable feeding table extension that is able to support paper up to 130 cm long.


ANTI-STATIC BAR

Pair of ionization bars that remove static charge from laminated paper.

*Important – the machine must be operated either with Reception unit or with Jogger.



Optional Jogger 530



Optional Foliant Foiler

Foliant Vega 530 SF			
Max speed	20 m / min	Warming up time	8 min
Max. performance	1720 B2 / hour	Temperature control	80 - 140°C
Feeding	Automatic	Power supply	3 ph., 3x400 V AC, 50-60 Hz
Feeding system	Suction feeding head	Power	5000 W
Feeder's load capacity	28 cm	Floor space with Jogger (w x l)	100 x 215 cm
Overlaps	In-Run Adjustable	Weight	400 kg
Overlaps accuracy	+ / - 2 mm	Dual de-curl bar, In-run adjustable	Standard
Separation	Automatic, Bump Rollers	Jogger 530	Optional
Paper weight	115 - 500 gsm	Reception Unit RU530	Optional
Main rollers pressure	Pneumatic	Non-sticky pressure roller	Optional
External compressor	6 - 8 bar, 150 l/min	Pneumatic separation	Standard
Min. sheets size (w x l)	20 x 30 cm	Air shaft	Optional
Max. sheets (w x l)	53 x 75 cm	Foliant Foiler	Optional