



LST03II-0806-RM **Table de découpe**



- ✓ **Systeme de positionnement visuel QR**
- ✓ **Fournir une solution complete**
- ✓ **Systeme d'aspiration d'air sous vide**
- ✓ **Plusieurs outils de coupe pour repondre a de multiples besoins**
- ✓ **Ceinture en feutre roulante sans couture**
- ✓ **Alimentation precise, rend l'assemblage ligne ordonnee**



Parameters

JWEI reserve the rights of final explanation, no further information for any exchanging.

Type	LST03II-0806-RM
Auto feeder	
Auto sheet capacity	<100mm
Feeding system	Vacuum feed with clamps mounted on gantry
Max. sheet size	800MMX600MM
Min. sheet size	210MMX297MM
Standard tools	CCD camera, electric oscillating tool, full-cut tool, half-cut tool, creasing wheel,
Optional	Bevel cutting tool, Creasing wheel tools for corrugated board
Cutting system	
Productivity	15 secs - 45 seconds per SRA3 sheet (average 24 seconds - depending upon complexity) 70 sec/B2 sheet (varies depends on complexity of material)
Max. cutting speed	1200mm/s
Cut thickness	≤6mm
Repeat accuracy	±0.1mm
Software and connection	
File form	PLT、DXF、XML、CF2
Interface	Ethernet Port
Connection	LAN
Green Credentials	
Voltage	220V±10%/50HZ
Power	4KW
Weight	380KG
Size	3200mmx1100mmx1100mm