



## **LST03II-0912-RM** **Table de découpe**



- ✓ Amélioration des performances
- ✓ Automatique et sans surveillance
- ✓ Jwps et Qr Système de positionnement
- ✓ Module de tête de machine intelligente
- ✓ Protection de sécurité multiple
- ✓ Solution préférée pour les commandes personnalisées à court terme



# Parameters

JWEI reserve the rights of final explanation, no further information for any exchanging.

Type	LST03II-0912-RM
Max. Sheet Size	900*1200mm
Min. Sheet Size	210*297mm
Max. Loading	≤180mm, Max. 400 Kgs
Max. Moving Speed	1500mm/s
Max. Cutting Speed	1200mm/s
Max. Cutting Thickness	≤6mm
Repeat Precision	±0.1mm
Standard	Basler CCD camera, Plotting pen, Laser locating pointer, Passive cutting tool, Active cutting tool, Electric oscillating tool, Creasing wheel tool,
Optional	Creasing wheel tool/ Dual V-Cut tool / Press cutting tool / Roll to sheet device / JWPS packaging software
Individual vacuum zones	4
Safe device	Infrared sensor, mechanical collision-prevention device(* Optional)
Controller	M5
Transmission system	Synchronous belt
Control system	Servo driver (4 sets)
Interface	Ethernet port
Software	JWCS, QR code system included
File format	DXF, PLT, PDF, HPGL, XML, CF2, AAMA, NC, EPS
Rated power	6.5 Kw
Power supply	Single phase 220V±10%, 50/60Hz
Noise range	75-90 dB
Operating environment	10-35°C, 10-80% humidity
Machine dimension	2598x1975x1148mm (Without collecting platform)
Machine weight	700 KGS